



Note:

1. Vista must be set using the timer (03/23185/0) MODE button to MAN ON for end of line testing and remain in that mode delivered to end customer.
2. Timer plastic battery insulation tab must be pulled out and left off following end of line inspection.
3. Timer screen protector needs to be removed.
4. SD Card (100001538) must be left inserted into media board.
5. EU kettle lead and plug must be fixed to the product and the UK kettle lead plug is part of the accessory kit.
6. Timer decorative cover to be included as part of the accessory kit.
7. No Low voltage wires should be wire tied to high voltage wires.
8. When wiring the screen to the media board, using wire (100001720) this needs to be earthed to the media board by fixing with a M3 machine screw and shake proof washer.
9. Mirrored glass top fixing bracket (300004039) needs to be fitted using a jig or the mirrored glass to ensure the gap is correct to allow the installation of the mirrored glass (100001447) by the end customer.

ISSUE	MODIFICATIONS	OCN	APPD	DATE	NOTES
1	Released for production.	---	D.Kiely	16/10/24	

DO NOT SCALE
IF IN DOUBT ASK

THIRD ANGLE PROJECTION

GLEN DIMPLEX RESEARCH & DEVELOPMENT
HEATING AND VENTILATION IRELAND
Barn road, Dunleer, Co.Louth, Ireland. Tel: +353(0)41 6872000

DRAWN BY D.Kiely	DATE 16/10/2024	SCALE 0.150	HOLE TOL +/-0.05	GEN TOL 0 +/-0,4
APP'D BY N/A	DATE N/A	DIM IN mm	ANGLES +/-0.5°	0,0 +/-0,2 0,00 +/-0,1

MATERIAL
See other parts

FINISH
See individual parts.

R.o.H.S. and POP compliant
All materials must comply with the requirements of European Directive 2015/863/EU (RoHS) and Regulation No. 2019/1021 (POP) on the restriction of the use of certain hazardous substances

THIS DRAWING IS SUPPLIED IN CONFIDENCE AND THE COPYRIGHT THEREOF IS THE PROPERTY OF GLEN DIMPLEX: IT MUST NOT BE USED BY A THIRD PARTY WITHOUT PRIOR PERMISSION. © 2023

PROJECT
Vista 130-I

TITLE
130-I Assembly

NO. OFF: 1

DRG NO
300004310

A3
Sht 1 of 1